

PowerFibers Thin-Film Batteries on Fiber Substrate

Science And Technology
For A Better World

Bernd J. Neudecker and Martin H. Benson

ITN Energy Systems, 8130 Shaffer Parkway, Littleton, CO 80127, USA

DARPA Synthetic Multifunctional Materials (SMFM) Program
Dr. Leo Christodoulou, DARPA, SMFM Program Manager
Dr. Steven Fishman, ONR, COTR











maintaining the data needed, and of including suggestions for reducing	lection of information is estimated to completing and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar DMB control number.	ion of information. Send comments arters Services, Directorate for Information	regarding this burden estimate mation Operations and Reports	or any other aspect of the 1215 Jefferson Davis I	is collection of information, Highway, Suite 1204, Arlington	
1. REPORT DATE 2003		2. REPORT TYPE N/A		3. DATES COVE	RED	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
PowerFibers - Thin-Film Batteries on Fiber Substrate				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S)				5d. PROJECT NUMBER		
					5e. TASK NUMBER	
				5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) ITN Energy Systems, 8130 Shaffer Parkway, Littleton, CO 80127, USA				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)		
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT ic release, distributi	on unlimited				
13. SUPPLEMENTARY NO The original docum	otes nent contains color i	mages.				
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	UU	17	RESPONSIBLE PERSON	

Report Documentation Page

Form Approved OMB No. 0704-0188

The Concept: PowerFiber ⇒ PowerComposite





Objectives:

- 1) Fabricate solid-state thin-film batteries directly onto structural fibers
- 2) Incorporate these "PowerFibers" into structural composites and fabrics

"PowerFiber"

"PowerComposite"















Energy, Power (Thin-Film Batteries) = Proportional to Battery Area!




Substrate Area: Foil vs. Fiber Stack

Double-sided foil substrate (50 μ m thick) = 2 cm²

1 Layer of fibers (50 μ m in dia.) = 3.14 cm² (57% more area)

2 Layers of fibers (25 μ m in dia.) = 6.28 cm² (214% more area)

3 Layers of fibers (17 μ m in dia.) = 9.42 cm² (371% more area)












PowerComposite Applications














ITN's ElectroTextiles Concept: PowerFiber ⇒ PowerWeave














"Li-Free" Battery Configurations Cathode (+) = Only Initial Li Source





"Li-Free"

Cathode (+)
Electrolyte
Plated Li
Cu acc (-)

"Buried Li-Free"













"Li-Free" PowerFiber on Sapphire





■ First PowerFiber (February 2001)



- Lithium-Free Battery Configuration
- 1.3 μm a-Li_{1.6}Mn_{1.8}O₄ Cathode (Li source)
















SEM Micrograph of "Buried Li-Free" PowerFiber on SiC Fiber

















PowerComposite with 10 PowerFibers inside PET Matrix
















PowerComposite: Electrochemical Testing under Deformation














PowerComposite ("Buried Li-Free" with Li₂V₂O₅ Cathodes)














PowerComposite ("Buried Li-Free" with Li₂V₂O₅ Cathodes)

















Cathodes (+) Determine Energy and Power! Also: Voltage, Power, Weight, and Volume

Year		ntive Discharge gy @ > 1 mA/cm²
2001	amorphous Li _{1.6} Mn _{1.8} O ₄	1
2002	amorphous & crystalline Li _x V ₂ O ₅	10
2002	crystalline LiCoO ₂	> 100










PowerComposite: "Li-Free" and LiCoO₂ Cathodes














PowerFiber Rate Capability: "Li-Free" and LiCoO₂ Cathodes



■ 1 mWh and 39 mW per 7m (23 feet) PowerFiber (Ø100 µm)











PowerFiber Technology Summary — Conclusions — Outlook



- ITN's Thin-Film Batteries @ 100% DOD
 - □ >2,000 demonstrated for PowerFibers (with challenging "Li-free"!)
 - □ >90,000 demonstrated for flat configuration (38% overall capacity loss)
 - □ Battery operation demonstrated between 45°C to +120°C
 - □ Battery life-time commensurate with device life-time

Very Safe Inorganic Battery Technology

- □ No fuming, no outgassing, no burning, no explosion, no thermal runaway
- Only limited local heat generation in case of accident
 -] Small battery mass per unit length of fiber
- □ Controlled heat dissipation in PowerFiber network
 -] Vastly spread-out heat sink

■ Payoffs for Space and Aviation Applications

- □ Spacecraft structure itself becomes a battery (increases payload)
- □ Distributed power storage (power structure is "everywhere" in space bus)









Acknowledgments



Funding

DARPA Synthetic Multifunctional Materials (SMFM) Program

Dr. Leo Christodoulou, DARPA, SMFM Program Manager

Dr. Steven Fishman, Office of Naval Research (ONR), COTR

Co-Workers

Dr. Joseph Armstrong (ITN)

Brian Emerson (ITN)

Paul DuPont (ITN)

Dr. Tony Zahrah (Matsys, Inc., VA, USA)

Dr. Haydn Wadley & Team (University of Virginia, VA, USA)







